





TECHNICAL DETAILS OF ULTRA VIOLET COATED PANELS (EXTERIOR GRADE)



UV COATED PANELS

(HARD WOOD USED FOR MOTHERBOARDS)

Cutting Equipment:-

The ideal cutting equipment shall be a Panel Saw with a primary Cutting blade & a secondary scoring blade. The Cutting motor shall drive the Primary cutting Saw between 5500 RPM – 7000 RPM

Primary Cutting Blade Specification:- Shall be with 72 Teeth with PCD / TCD Tip.

The Feed Rate: A Steady feed rate is essential for the perfect cut without chipping of unevenness on the edges. The feed rate shall be 18 ft per minute.

Panel Saw Preparedness before cutting:-

- The Primary cutting blade and the scoring blade have to be in perfect alignment to give a 90 degree cut edge.
- The Blade sharpness needs to be checked
- The Cutting Table cleaned out of all dust / cutting residue to avoid accidental scratches to the Panel

Critical Points to be noted

- Do not Peel Off the BOPP protective film from the board till your fabrication process is not over.
- Once the BOPP film is removed please wipe clean the surface of the board with any cleaning agent like Colin.

Best Cutting Process

- Place the UV Coated Board with the BOPP film on the cutting tray.
- UV Coated MDF Board Gloss surface side should be facing towards Scoring Saw.
- Align the board edge to the horizontal guide for a perfect straight edge.
- Align Primary & Scoring blades.
- Set Blade Speed to 7000 RPM (Min. 5500 RPM)

- Push the board @ constant speed of 18 ft per minute.
- Ensure that the dust collector is turned on the effectively clean the work space.
- Use Protective work Gloves & Glasses while cutting the board.

Technical Specifications

- 9 Layers of High Gloss UV Lacquer The Action Tesa Ultra Violet Coated Panels are coated with 9 Layers of UV Lacquer rendering an impervious and permanent high gloss surface.
- Exterior Grade Core Exterior Grade Core Panel used high water resistance making it ideal for application in moisture prone areas & also used for all furniture application.
- Highly Scratch Resistant Highly Resistant to abrasion with a UV Hardened surface.
- Gloss Level Transparent UV Lacquer render more than 95 degree Gloss Level that does not lose its sheen with the passage of time. Increased sharpness & depth of décor.
- Environment Friendly Environment Friendly Paneling Solution with 0.05mg/L of Formaldehyde Emission, Zero VOC & has no Benzene or lead content
- Resistant to Acids & Alkalies Resistant to most Acids, Alkalies & Stains
- Surface Hardness 2H 3H
- Hard Wood Hard Wood used for Mother Boards.

Hard Wood – Hard Wood us Best Application Concepts

- Cupboard Shutters Ideal for Cupboard Shutter that enriched the Interiors
- Kitchen Shutters Ideal for Kitchen Shutters with the Ultra High Gloss that's easy to maintain, is Water Resistant, Flame Resistant & Scratch Resistant
- Toiled Cabinet Shutter With High Resistance to Moisture / Water Resistant factor UV Coated Panels are best choice for Vertical toiled Cabinet Shutters

- Partition Panels Create Relief Sections in an otherwise Mundane Partition Section, It can be also used for Partition Panels for Double & Single skin Partition Panels. The High Gloss lends depth to the partitioned area.
- Furniture Embellishments Can be used to Clad Drawer facia & Furniture Vertical Section, It's best used as Embellishments.
- Wall Paneling Can Lend depth to with graceful Interiors

Note – Action TESA Ultra Violet Coated Panels are best suited for any Vertical Application.

Edge Finishing the Panels

 Action TESA Supplied PVC High Gloss finished Edge Band Tape which is available in 150 Meter Rolls in complimenting ranges. The Edge Band Tapes can be fixed with a thru-feed machine. There is however the option of Aluminium profiles too which can be fitted with a groove on the edge.



















Balaji Action Buildwell Pvt. Ltd.

Regd. Office: G-11, Udhyog Nagar, Peeragarhi,
New Rohtak Road, North West Delhi, Delhi - 110 041 Ph.: 011-41120000, 41120020
Plant: Plot No. C34, C34 (A) to (D), C3, C6 (A) to (C), Eldeco SIDCUL Industrial Park, Sitarganj,
Distt. Udham Singh Nagar, Uttarakhand - 262405

Customer Care Service: 1800 309 07 07

customerservices@actiontesa.com

www.actiontesa.com